



SIZE	ART. NO.	EAN NO.
6	991-6	7392626064430
7	991-7	7392626021174
8	991-8	7392626021181
9	991-9	7392626021198
10	991-10	7392626021204
11	991-11	7392626021211

TEGERA® 991

Cut resistant glove, PU, palm-dipped, Dyneema®, glass fibre thread, nylon, 13 gg, smooth finish, cut resistance level 5, Cat. II, grey, water and oil repellent palm, for precision work

PROPERTIES

Good fingertip sensitivity, very durable, good grip, good fit, comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 5

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 13,2

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINER MATERIAL Dyneema®, glass fibre thread, nylon, 13 gg

DIPPING Palm-dipped

DIPPING MATERIAL PU

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 230 - 260mm

COLOUR Grey

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bag

MATERIAL SPECIFICATION Polyurethane 40%, UHMWPE 40%, glass fibre thread 10%, nylon 10%

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 991

FEATURES

Cut resistant according to EN 388:2003 level 5, cut resistant according to 388:2016 level C

PRIMARY PROTECTION

Prevents risk of: cut injuries, abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, oil and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, installation work, electrical installation, HVAC installation, sheet-metal work, construction, soil preparation, warehouse work, airport work, metalwork, mining, glass industry work, wood industry work, repair work, decontamination, sanitation

PRIMARY INDUSTRIES OF USE


Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, automotive, transportation, utilities, building and construction

TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-30

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 991

EC TYPE EXAMINATION

Notified Body: 0161 Aitex, Plaza Emilio Sala, 1, E-03801 ALCOY (Alicante) Spain

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	5	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	4	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-30

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com